

## M-POWER-2T


# MORMAX

Mormax Company, Inc.

914-699-0101



### 8 Westchester Plaza



### M-POWER-2T-D-BTP

Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

#### Trim Plate Finish:

#### **BLACK POWDER COATED (STEEL)**

**AC POWER & DATA CONNECTIVITY SOLUTION** 

Custom Finishes Available

M-POWER-2T-D-BTP



#### Features:

#### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- B Double USB (Fast Charging Ports Rated for 3.2A)
- C HDMI
- D CAT 6
- E 3.5mm Mini Stereo Jack
- F Single USB (Fast Charging Port Rated for 3.2A)
- G RJ 12
- H Switched AC
- 3-Way Switch
- J USB-C (27W High Speed Charging Port)
- K USB-C (13W High Speed Charging Port)
- L Switched AC (Rocker Switch)
- M AC Dimmer

#### Plug:

Low Profile Flat 45° Angle 120 VAC Plug Standard Straight 120 VAC Plug

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 3.2A HIGH SPEED USB CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- ETL LISTED FOR MOUNTING IN FURNITURE
- 15A
- 0% TO 100% DIMMING





# M-POWER-2T

## MORMAX

Elmsford, NY 10523

Mormax Company, Inc. **AC POWER & DATA CONNECTIVITY SOLUTION** 

8 Westchester Plaza

914-699-0101

sales@mormax.com mormax.com

M-POWER-2T-D-BTP

Specs: **Modules/Ports:** AC Dimmer TOP 2.000" (50.800mm) 2.106" (53.503mm) 4.759" (120.903mm) Shown with 1 AC Dimmer. 0.619" (15.746mm) 1.233" (31.340mm) 0.613" (15.594mm) 2.000" (50.800mm) D 1.132" (28.766mm) 0.582" (14.800mm) 0.669" (17.000mm) 0.093" (2.381mm) 0.140" (3.563mm) 0.234" (5.944mm) 0.118" (3.000mm) 1.840" (46.744mm) .606" (40.800mm) END SIDE 0.905" (23.000mm) 1.555" (39.503mm)