

# M-POWER-3T

# **AC POWER & DATA CONNECTIVITY SOLUTION**

3TW-AU7-APATE

Distributed by



Mormax Company, Inc.

8 Westchester Plaza Flmsford, NY 10523 sales@mormax.com

mormax.com


Metro Light & Power's line of power & data solutions offers sophisticated design elements combined with greater ease of installation. Streamlined and low-profile, enhanced by side-exiting cords, our outlets advance the industry with their cutting-edge look and feel. We believe flexibility is key, and we provide a variety of mounting options, including the ability to mount in limited spaces. Our outlets are available in many finishes and configurations, in addition to a custom color and finish capability for our clients.

#### Trim Plate Finish:

### **SPECIAL ANTIQUED BRONZE (ABS)**

Custom Finishes Available M-PC

M-POWER-3TW-AUZ-APATP



## Features:

### **Module/Port Options:**

- A Tamper Resistant AC Receptacle
- U Double USB (Fast Charging Ports Rated for 3.2A)
- H HDMI
- 6 CAT 6
- 12 RJ 12
- X Switched AC
- Y 3-Way Switch
- C USB-C (27W High Speed Charging Port)
- Z USB-C (18W High Speed Charging Port)
- R Switched AC (Rocker Switch)

#### Plug:

Supplied with Low Profile Flat 45° Angle 120 VAC Plug

Optional Standard Straight 120 VAC Plug

Optional Straight 120 VAC Pass-through Plug

Shown in Special Antiqued Bronze (ABS) Plate, featuring 1 Tamper Resistant AC, 1 Double USB Charging Port, and 1 USB-C Charging Port.

- CLEAN, COMPACT DESIGN
- STREAMLINED
- LOW PROFILE
- SIDE-EXITING CORDS
- PLUG & PLAY
- 18W HIGH SPEED USB-C CHARGING FOR ALL DEVICES
- 3.2A HIGH SPEED USB CHARGING FOR ALL DEVICES
- 6' AC CORD & PLUG (FLAT PLUG STANDARD)
- CUSTOMIZABLE CONFIGURATIONS AND FINISHES
- UL LISTED FOR MOUNTING IN FURNITURE
- 15A





Mormax Company, Inc.

914-699-0101 sales@mormax.com


8 Westchester Plaza Elmsford, NY 10523

mormax.com

**Modules/Ports:** 

- Tamper Resistant AC Receptacle
- U Double USB (Fast Charging Ports - Rated for 3.2A)
- USB-C (18W High Speed Charging Port)

TOP



0.118" (3.000mm) 1 SIDE 0.905" (23.000mm)